

Master Bodyworker™



TOP:

Top design	Two piece, folding, round corners, 3-layer foam
Standard size	30" x 73"
Foam	3/4" firm bottom, 1- 3/4" medium-density middle, urethane polymer
Polyester batting	1/2" fluffy polyester Dacron top layer
Frame	3/4" x 1-3/4" poplar rails, 3/16" plywood top, poplar blocks

TOP OPTIONS:

Deep tissue foam	3/4" firm bottom, 2" medium-density middle layer, 1/2" Dacron top layer
Widths - custom	33" (maple legs are standard)
Crescent insert & plug	11.5" diameter centered hole starting 3" from table end
Pregnancy option	18-3/4" x 15-1/2" centered egg-shaped hole starting 8" from table end
Sidearms	Holes are not standard and table must be ordered with holes
Armrest/footrest combo	Only attaches to one end of table, Used on end with a low endplate





VINYL CHOICES:

Ultra Soft Touch - standard	Lightly textured, Super Soft Urethane vinyl, fabric backed, environmentally friendly
-----------------------------	--

LEGS:

Height range - standard	Quick-open CenterLock leg system with Hi-low end plates 24" to 34" (medium) 9 positions
4" leg recess	4" recess from ends of table
Hi-low end plates	Allows for extra leg room at one end
Low end plate position	15" knee space between bottom plate and lower table edge
High end plate position	8" from the table top to the lower plate edge
Pocketed leg blocks	Adds superior load-bearing capacity
Leg room - width (30" table)	21.75" inside distance between legs at end of table
Leg design	Quick open, no pins, nylon fittings connect leg parts
CenterLock Legs	1" x 1-3/8" maple legs, 3/4" diameter wood dowels
Cables	3/32" steel (49 wires) PVC-coated (1/8" O.D.)
Cable end crimps	Tested to over 1500 lbs. pull



LEG OPTIONS:


High range legs	26" to 36"
-----------------	------------

GUARANTEES:

Structure	5 yrs
Foam & Vinyl	Guaranteed to arrive in good condition

WEIGHTS:

Weight 30" x 73"	34 lbs.
Shipping weight - boxed	40 lbs 40" x 32" x 10" (for 30" x 73")



Rev 8/18/08



PO Box 1304 Dimmocks Mill Rd
International: 919.732.6968

Toll Free: 800.678.6824

Fax: 919.732.1173