



# Olympus™ Salon Top

## SALON TOP:

<b>Foam</b>	<b>Four-section upholstered top, square corners, 3 layer foam</b>
<b>Polyester batting</b>	3/4" firm bottom, 1- 3/4" medium middle, urethane polymer
<b>Upholstered top &amp; frame</b>	1/2" fluffy polyester Dacron top layer
<b>Subframe</b>	30" width x 67" length x 4.5" thickness
<b>Leg Frame</b>	25" width x 60" length x 2" thickness
<b>Adjustments</b>	20.5" width x 56.5 length x 5" thickness
<b>Back tilt angle</b>	Manual adjustments on knees and back, lies flat for massage
<b>Knees &amp; feet tilt angles</b>	6 positions from 0° to 40°
	Knees - 2 positions 0° or 21°, Feet - 2 position 0° or 5" from subframe top

## TOP OPTIONS:

<b>Footrests and face supports</b>	No extra holes needed - Deluxe FaceSpace II recommended for prone massage
<b>Salon headrest</b>	6" x 15" x 2.5" thick pad with 6" x 8.5" x 3" thick rounded, movable pillow
<b>Elevating side arms</b>	4" x 15" x 2.5" thick, removable and adjustable height
<b>Salon footrest</b>	4" x 15" x 2.5" thick

## VINYL CHOICES:

<b>Ultra Soft Touch - standard</b>	Lightly textured, Super Soft Urethane vinyl, fabric backed, environmentally friendly
------------------------------------	--

## BASE:

<b>Outside leg spacing</b>	<b>Maximum leg and knee room and maximum height range</b>
<b>Inside leg spacing</b>	25" width x 56" length
<b>Base materials</b>	20" width x 51" length
<b>Parallel Lift Bars</b>	Maple legs with 3/4" plywood
<b>Adjustable leg extension</b>	Two powder-coated carbon steel lift bars connect to motor
<b>Height range</b>	1/4" leg bolts w/ 2 knobs, 11 holes, felt backed, 2 rubber bumpers per leg
<b>Leg Recess</b>	19" to 41" Double adjustable: 10" manual (ext. legs) & 12" electric lift
	2" Recess on sides, 11" recess from head section

## ELECTRIC LIFT:

<b>Lift mechanism</b>	One 24 volt motor/actuator powered through a 110 volt, 5 amp transformer
<b>Motor - Linak or Dewart</b>	24 VDC permanent magnet motor, UL listed
<b>Power consumption</b>	Linak, 4 amps; Dewart 5 amps max.
<b>Control</b>	Foot pedal
<b>240-volt model (international)</b>	Available at extra charge

## BASE OPTIONS:

<b>Extra-low-range legs</b>	16.5" to 24" (electric lift only, short non-adjusting legs replace ext. legs)
-----------------------------	---

